

Price list of lighting products, Silver series

June 2022



In the name of the Creator of Light

Thank you in advance for your good attention and trust in the products of Shayan Bargh Industrial Group.

Please note the following before reading the price list:

1. An additional 9% VAT has been added to the price of all products.
2. The price of the products mentioned in this booklet is calculated and presented based on the factory door delivery (without installation).
Obviously, the prices can also be offered taking into account the installation price.
3. All products have warranty and after-sales service. Of course, factors such as improper use, installation by non-specialists, voltage changes, natural disasters and theft are not covered by the warranty.
4. Shipping cost from the factory door to the buyer's desired location is with the buyer.
5. Due to price fluctuations, please contact the sales unit of Shayan El Berq Industrial Group to know and ensure the latest price changes of products.

Product list



LED Street Lights	1
LED Flood Lights	8
LED Garden Lights	13
LED High Bay Lights	16

LED Street Lights

LED Street Lights - Ramand



SH-SL-100S-R-S	SH-SL-50S-R-S	SH-SL-30S-R-S	SH-SL-20S-R-S	Code
Ramand	Ramand	Ramand	Ramand	Name
100	50	30	20	Pawer (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
48	48	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Constant Current	Driver Type
SMD LED	SMD LED	SMD LED	SMD LED	Type of Light Source
11000	5500	3300	2200	Luminous Flux (Lm)
50000	50000	50000	50000	Nominal lifetime (hrs)
IP66	IP66	IP66	IP66	Degree of Protection
Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
5.5	3.15	3	3	Weight (kg)
490*275*75	385*215*75	385*215*75	385*215*75	External Dimensions (mm)
				Picture
82.50	47.50	45.00		Price (\$)

LED Street Lights - Ramand

Price list of lighting
products, Silver series






LED Street Lights - Himalaya



SH-SL-200S-H-S	SH-SL-150S-H-S	SH-SL-100S-H-S	SH-SL-75S-H-S	SH-SL-50S-H-S	SH-SL-30S-H-S	Code
Himalaya	Himalaya	Himalaya	Himalaya	Himalaya	Himalaya	Name
200	150	100	75	50	30	Power (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
48	48	48	36	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Driver Type
SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	Type of Light Source
22000	16500	11000	8250	5500	3300	Luminous Flux (Lm)
50000	50000	50000	50000	50000	50000	Nominal lifetime (hrs)
IP66	IP66	IP66	IP66	IP66	IP66	Degree of Protection
Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
9.1	8.4	4.1	4.1	4	3.9	Weight (kg)
435*245*105	435*245*105	435*245*105	435*245*105	435*245*105	435*245*105	External Dimensions (mm)
						Picture
123.21	106.79	77.50	70.36	57.14	50.36	Price (\$)






SH-SL-80H-S	SH-SL-50H-S	SH-SL-30H-S	Code
Dena	Dena	Sahand	Name
80	50	30	Pawer (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
30-36	12	30	Operating voltage of LED module (Vdc)
Constant Current or Constant Voltage	Constant Current or Constant Voltage	Constant Current or Constant Voltage	Driver Type
High Power LED	High Power LED	High Power LED	Type of Light Source
8000	5000	3000	Luminous Flux (Lm)
50000	50000	50000	Nominal lifetime (hrs)
IP65	IP65	IP65	Degree of Protection
Die cast aluminum body with Integrated Mold	Die cast aluminum body with Integrated Mold	Die cast aluminum body with Integrated Mold	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
8.4	8.4	3.5	Weight (kg)
700*280*64	700*280*64	480*230*60	External Dimensions (mm)
			Picture
does not exist	does not exist	does not exist	Price (\$)

LED Street Lights – Shahbaz, Modular Shahbaz

Price list of lighting products, Silver series



SH-SL-150S-S	SH-SL-100S-S	SH-SL-150H-S	SH-SL-100H-S	Code
Modular Shahbaz	Modular Shahbaz	Shahbaz	Shahbaz	Name
150	100	150	100	Power (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
36	36	30 - 36	30 - 36	Operating voltage of LED module (Vdc)
Constant Current or Constant Voltage	Constant Current or Constant Voltage	Constant Current or Constant Voltage	Constant Current or Constant Voltage	Driver Type
SMD LED (Philips)	SMD LED (Philips)	HIGH POWER LED	High Power LED	Type of Light Source
15000	10000	15000	10000	Luminous Flux (Lm)
50000	50000	50000	50000	Nominal lifetime (hrs)
IP65	IP65	IP65	IP65	Degree of Protection
Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Degree of Protection
9.3	8.8	8.5	8.4	Body Material
737*302*70	700*280*64	737*302*70	700*280*64	Working Temperature Range(°C)
				Picture
does not exist	does not exist	does not exist	does not exist	Price (\$)

LED Street Lights - Taftan




SH-SL-100C-S	SH-SL-50C-S	SH-SL-35C-S	Code
Taftan	Taftan	Taftan	Name
100	50	35	Power (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
24	24	36 - 30	Operating voltage of LED module (Vdc)
Constant Current or Constant Voltage	Constant Current or Constant Voltage	Constant Current or Constant Voltage	Driver Type
COB LED	COB LED	COB LED	Type of Light Source
10000	5500	3500	Luminous Flux (Lm)
50000	50000	50000	Nominal lifetime (hrs)
IP65	IP65	IP65	Degree of Protection
Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
5.7	3	2.6	Weight (kg)
723*282*95	500*215*85	400*156*56	External Dimensions (mm)
			Picture
116.07	77.14	does not exist	Price (\$)

LED Flood Lights

LED Flood Lights - Ramand



SH-FL-100S-R-S	SH-FL-50S-R-S	SH-FL-30S-R-S	SH-FL-20S-R-S	Code
Ramand	Ramand	Ramand	Ramand	Name
100	50	30	20	Power (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
48	48	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Constant Current	Driver Type
SMD LED	SMD LED	SMD LED	SMD LED	Type of Light Source
11000	5500	3300	2200	Luminous Flux (Lm)
50000	50000	50000	50000	Nominal lifetime (hrs)
IP66	IP66	IP66	IP66	Degree of Protection
Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
5.5	3.15	3	3	Weight (kg)
400*275*75	345*220*60	345*220*60	345*220*60	External Dimensions (mm)
				Picture
82.50	47.50	45.00		Price (\$)

LED Flood Lights - Himalaya

Price list of lighting products, Silver series



SH-FL-200S-H-S	SH-FL-150S-H-S	SH-FL-100S-H-S	SH-FL-75S-H-S	SH-FL-50S-H-S	SH-FL-35S-H-S	Code
Himalaya	Himalaya	Himalaya	Himalaya	Himalaya	Himalaya	Name
200	150	100	75	50	30	Power (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
48	48	48	36	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Driver Type
SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	Type of Light Source
22000	1650	11000	8250	5500	3300	Luminous Flux (Lm)
50000	50000	50000	50000	50000	50000	Nominal lifetime (hrs)
IP66	IP66	IP66	IP66	IP66	IP66	Degree of Protection
Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
9.5	8.9	4.1	4.1	4	3.9	Weight (kg)
475*385*135	475*385*135	380*245*105	380*245*105	380*245*105	380*245*105	External Dimensions (mm)
						Picture
123.21	106.79	77.50	70.36	57.14	50.36	Price(\$)

LED Flood Lights - Himalaya



SH-FL-400S-H-S	SH-FL-300S-H-S	Code
Himalaya	Himalaya	Name
400	300	Pawer (w)
170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
48	48	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Driver Type
SMD LED	SMD LED	Type of Light Source
44000	33000	Luminous Flux (Lm)
50000	50000	Nominal lifetime (hrs)
IP66	IP66	Degree of Protection
Cast aluminum	Cast aluminum	Body Material
+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
15.2	14.5	Weight (kg)
625*500*125	625*500*125	External Dimensions (mm)
		Picture
258.93	231.43	Price(\$)

LED Flood Lights – Almas, Modular Almas






SH-FL-200S-S	SH-FL-150S-S	SH-FL-200C-S	SH-FL-150C-S	SH-FL-100C-S	SH-FL-50C-S	Code
Modular Almas	Modular Almas	Almas	Almas	Almas	Almas	Name
200	150	200	150	100	50	Pawer (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
36	36	36	36	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Driver Type
SMD LED	SMD LED	COB LED	COB LED	COB LED	COB LED	Type of Light Source
20000	15000	20000	15000	10000	5000	Luminous Flux (Lm)
50000	50000	50000	50000	50000	50000	Nominal lifetime (hrs)
IP65	IP65	IP65	IP65	IP65	IP65	Degree of Protection
Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Aluminum die-cast with Integrated Mold	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
10.2	10	10.2	10.4	10	3.7	Weight (kg)
424*323.5*190	424*323.5*190	424*323.5*190	424*323.5*190	360.9*290*102.8	280*236*180	External Dimensions (mm)
						Picture
does not exist	does not exist	155.71	131.07	100.71	58.57	Price(\$)

LED Garden Lights

LED Garden Lights - Alborz



SH-GLA2-50-S	SH-GLA2-30-S	SH-GLA-30-S	Code
Pendant Alborz 2	Pendant Alborz 2	Standing Alborz	Name
50	30	30	Power (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
36	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Driver Type
High Power LED	High Power LED	High Power LED	Type of Light Source
5000	3000	3000	Luminous Flux (Lm)
50000	50000	50000	Nominal lifetime (hrs)
IP65	IP65	IP65	Degree of Protection
Cast aluminum	Cast aluminum	Cast aluminum	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
6.2	6.2	5.3	Weight (kg)
400*335	400*335	760*364*399	External Dimensions (mm)
			Picture
84.29	49.29	69.64	Price(\$)

LED Garden Lights – Zagros, Lona



SH-GLL-50-S	SH-GLL-30-S	SH-GLZ-50-S	SH-GLZ-30-S	Code
Luna	Luna	Zagros	Zagros	Name
50	30	50	30	Pawer (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
36	36	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Constant Current	Driver Type
High Power LED	High Power LED	High Power LED	High Power LED	Type of Light Source
5000	3000	5000	3000	Luminous Flux (Lm)
50000	50000	50000	50000	Nominal lifetime (hrs)
IP65	IP65	IP65	IP65	Degree of Protection
Cast aluminum	Cast aluminum	Cast aluminum	Cast aluminum	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
10	10	10	10	Weight (kg)
372*350	372*350	751*508	751*508	External Dimensions (mm)
				Picture
112.50	102.14	122.50	117.86	Price(\$)

LED High Bay Lights

LED High Bay Lights – Azar



SH-HB-200S-H-S	SH-HB-150S-H-S	SH-HB-100S-H-S	SH-HB-75S-H-S	SH-HB-50S-H-S	SH-HB-30S-H-S	Code
Himalaya	Himalaya	Himalaya	Himalaya	Himalaya	Himalaya	Name
200	150	100	75	50	30	Power (w)
170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	170-240 / 50-60	Input voltage range (V-AC/HZ)
48	48	48	36	36	36	Operating voltage of LED module (Vdc)
Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Constant Current	Driver Type
SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	Type of Light Source
22000	1650	11000	8250	5500	3300	Luminous Flux (Lm)
50000	50000	50000	50000	50000	50000	Nominal lifetime (hrs)
IP66	IP66	IP66	IP66	IP66	IP66	Degree of Protection
Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Aluminum die-cast	Body Material
+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	+50 ~ -20	Working Temperature Range(°C)
9.5	8.9	4.1	4.1	4	3.9	Weight (kg)
455*385*135	455*385*135	360*245*105	360*245*105	360*245*105	360*245*105	External Dimensions (mm)
						Picture
123.21	106.79	77.50	70.36	57.14	50.36	Price(\$)